

DESCRIPTION

Total thickness	EN 428	mm	2
Weight	EN 430	g/m ²	3100
Width of sheet	EN 426	cm	200
Length of sheet	EN 426	lm	20






CLASSIFICATION

Norm / Product specification	-	-	EN 685
European classification	EN 649	class	34 - 43
K rating	-	class	K5
Fire rating	EN 13 501-1	class	Bfl-s1
	DIN 4102	-	B1
	GB 8624-2006	-	GB 8624 Bf1-s1
Toxic testing	GB 18586-2001	-	OK
Static electrical propensity	EN 1815	KV	< 2
Electrical resistance	EN 1081	Ω	10 ⁹ - 10 ¹⁰
Slip resistance dry	EN 13893	-	≥0.3
Slip resistance wet	DIN 51 130	class	R9

PERFORMANCE

Abrasion resistance	EN 660.1	mm	≤0.15
Abrasion group	EN 649	group	P
Dimensional stability	EN 434	%	Sheet ≤ 0.4
Residual indentation	EN 433	mm	0.03
Thermal conductivity	EN 12 524	W/(m.K)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Chemical products resistance	EN 423	class	OK
Anti-bacterial and fungicidal	-	-	OK
Special maintenance treatment	-	-	PUR
Color number	-	-	18

CE MARKING 标识

	EN 14041	 抗静电	 防火	 供地下暖气设备使用	 防滑
---	----------	--	--	---	--